

Cutmatic[®] 45

Part No: MC108-0

Portable & Precise for Effortless Cutting

- ✓ CLEAN CUT 16MM

 ✓ SEVER CUT 20MM
- **✓ CUT MILD/STAINLESS STEEL, ALUMINIUM, COPPER & CAST IRON**
- **✓** AIR FILTER, WATER SEPARATOR **✓** SAFETY TRIGGER SWITCH
- **✓ POWER FACTOR CORRECTION (PFC) ✓ PILOT ARC START**





ACCESSORIES*	PART NO.			
Cutting Buggy	PLT009			
Circle Cutting Attachment Kit	PLT010			

^{*}Accessories sold separately.









Cutmatic[®] 45

Part No: MC108-0

MATERIAL	CUTTING THICKNESS			
	CLEAN	SEVER		
Mild Steel	16mm	20mm		
Stainless Steel	12mm	16mm		
Aluminium	10mm	12mm		


POWER FACTOR CORRECTION (PFC)

The machine has internal input power conditioning to smooth out the actual input current. With a smoother input current the machine is less demanding on generators and extension leads, thus increasing the options for remote site operation.*

*Refer to diagram below.

PILOT ARC START

Provides start method without the need for conventional HF start. The torch is designed to ignite the arc inside the torch head, producing a pilot plasma arc. The Plasma power then transfers from the torch to the job.





Clean Cut



Sever Cut

BUILT-IN WATER & AIR FILTER

Will remove any water in the air. This will increase the torch tip life.

DUTY CYCLE

Durable precision performing cutter with high 40% duty cycle allowing for long cutting runs at high ambient temperature.

PARKER SURECUT SCP40 TORCH

With an ergonomic handle to help prevent operator fatigue while the flexible cable makes manoeuvering easier and a safety latch for ultimate protection.

LED INDICATOR

For power, retaining cup status, air pressure and over temperature. Allows faster troubleshooting, eliminating unnecessary downtime.

PORTABLE

At only 11.5kg, the Cutmatic 45 is lightweight and portable, can easily be moved around the job site making it particularly useful for onsite demolition or maintenance.

15 AMP PLUG

240 V single phase operation with a 15 Amp plug will allow easy access to site power.

WARRANTY*

With a 3 year unlimited warranty, covering parts and labour, and supported by an Australia wide service network, you can be guaranteed you're buying reliability and performance.

*Power source only.



PRIMARY VOLTAGE		MAX. PRIMARY CURRENT	REC. GENERATOR kva	SUPPLY PLUG	RATED OUTPUT @ 40C (10 MIN)		CUTTING THICKNESS	SHIPPING WEIGHT	MACHINE WEIGHT
240 Vac - 50/60 Hz	14.2 A	22.5 A	6 kVA	15 A	45 A @ 40%	15 - 45 A	16mm	16kg	11.5kg





